

COLOUR VDS LOFT COMPACT MONITOR



Reference: 03753

Video door entry COLOUR monitor. TFT screen 3.5".

Installed in homes, lets you communicate with the outside panel, open the door and see the visitor on the built-in screen .

DESCRIPTION

Video door entry COLOUR monitor. TFT screen 3.5".

Installed in homes, lets you communicate with the outside panel, open the door and see the visitor on the built-in screen .

A new concept in monitors for the home. An integrated design, in line with new trends and lifestyles, simple and functional, combining quality and design. Purity of line, technology and performance make this equipment an elegant and perfect element for any home. Made in high impact ABS plastic, with a textured finish for easy cleaning and ultraviolet protection for greater resistance to sunlight. Loft Compact Monitor is the new Fermax hands-free push-to-talk monitor, unifying all the systems of a traditional monitor in a single circuit, with an unbeatable quality-price relation.

VDS system:

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video). Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit.

Maximum distance from first access to last home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "The door is open, please close the door behind you".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Maximum distance from first access to last home: 200 m.



TECHNICAL SPECIFICATIONS

Screen TFT 3.5".

Resolution: 480 (H) x 234 (V) lines.

Monitor dimensions: B/W: 240x133x55 mm (height-width-depth):Colour: 240x133x37 mm (height-width-depth):

Power supply: 18 Vdc

Door release and guard unit call button.

Auto-on button for main and secondary camera activation (sequentially).

Button to start communication.

Button to end communication.

Call volume control

Colour, brightness and contrast control.

Door bell: for direct house call button connection to monitor/telephone.

Selectable call tunes.

With 2 pushbuttons for additional functions (without functions assigned).

Private communication. Conversation secrecy.

Totally hands-free operation; once the outdoor panel-home channel is activated, communication is simultaneous.

Consumption: - in standby: 30 mA. - in call: 400 mA - active: 330 mA

Weight: 0,671686 kg

Size of product when packed: 26,8x16,5x7 cm

EAN 13: 8424299037530