

## SYNEL SY-04ST – Tripode turnstile gate



## Features:

- Main board owns manual function: Setting delay automatic door opening.
- Que Automatic opening after emergency fire signal input.
- Inti-following: prevent illegal passing.
- Que Auto replacement function, re-position after person passes by.
- Anti-tail function auto lock once turns 120 degrees.
- **@** Arms auto drop when power off, insure unblocked when accident.
- Standard electronic interface, remote control through internet which is also could connect variety card readers and receive relay signal to work.

Diverse control mode optional, changeable due to varying, convenient for your Manage.

- Que Auto alert error function, comfort for user maintain and operate.
- Manual button or remote control IR, Bi-directional passage
- Open signal with memory or without set function

## Synel order number -SY-04ST – 155092

Power voltage	AC220±10%,50Hz	Open angle	120°
Drive voltage	AC12V+AC18V	Pass speed	≦30 person/minutes
(Operation condition)	-15°C ~ +60°C	Structure	SS304 Stainless steel
Relative humidity	≦95%,None-condensation	Open direction	Single and Double (optional)
Input signal	12v DC level or 12v pulse>100ms	Work environment	Outdoor and indoor
Working Current	≤2000mA	IP Degree	IP43
Length of the bar	510mm	Width of passage	≤550mm
Service life	≥5 million times	Machine sizes	1200*280*980 mm

חטיבת הביטחון - סינאל סקיוריטי משה אביב 6, אור יהודה טל": 03-6346360 | פקס 03-6346360 www.anteco.co.il <u>,info@anteco.co.il</u> רח' התדהר,3, בית המילניום א.ת רעננה מיקוד 4366505, ת.ד 43 טל<sup>י</sup> 03-7555101 | פקס 03-7555101 www.synel.co.il ,<u>info@synel.co.il</u>

רח' המדע, 2, בית סינאל, יקנעם עלית מיקוד 2066719, ת.ד 142 טל' 04-9596777 | פקס www.synel.co.il ,info@synel.co.il

## Technical parameters