

COLOUR DUOX VEO MONITOR 4,3"



Reference: 09405

Video door entry COLOUR monitor. TFT screen 4.3"

Installed in homes, lets you communicate with the outside panel, open the door and see the visitor on the built-in screen.

DESCRIPTION

Video door entry COLOUR monitor. TFT screen 4.3"

Installed in homes, lets you communicate with the outside panel, open the door and see the visitor on the built-in screen.

The **new VEO monitor** is even simpler and more functional. A synthesis that takes design and performance to their most essential expressions, in a monitor specially designed for those users who decide to take the leap into video.

A new member in the home for those seeking **comfort and ease** when communicating.

The VEO monitor is made of high-impact ABS plastic. Texturised finish for easy cleaning and ultraviolet protection to get more resistance to the light.

VEO incorporates a 4,3" colour TFT screen. Its unique handset design incorporating a magnet enables the user to put it back into position correctly when the call is finished.

Its balanced design of pure lines is distinguishing, modern and minimal. VEO integrates in the ambience of any contemporary interior design.

DUOX System:

this is the first completely digital system in two-wire non-polarized technology. This is the most technologically advanced system in the world, allowing fast installation with just two wires. The most highly simplified and advanced installation system on the market. It maximizes intercom system capacities thanks to digital audio and video transmission.

Duox offers maximum ease of installation, enabling transmission of all signals: power feed, audio, video and data with the highest capacities.

It permits management of

- From 1 to 999,999 apartments:
- Calls from pushbutton panel: 99.
- Calls from keypad panel:
- Sub-block: 99.

- Block: 9999.
- General entry: 999999.

- From 1 to 10 panels:
 - Number of panels:
- General entry: 10.
- Block: 10.
- Sub-block: 10.

The maximum distance will depend on the installation topology and cable. See table of sections and distances for more details.

DUOX offers maximum versatility thanks to the stability and strength of signal transmission in this fully digital system which avoids possible feedback and interference in the installation.

The DUOX amplifier includes a voice synthesizer. Operating the lock release issues a message: "door open, close after entry".

Up to three terminals (telephones/monitors) can be installed in each apartment.

Apartment terminals require simple programming. This programming assigns a call code to each terminal.

Communication is private.

Cables:

Any type of cable may be selected: parallel, twisted pair and UTP CAT5 in new installations; even existing cables in replacement work can be used (5 wires, 2-wire bell or old 4+N wire).

Non-polarized 2-wire.

Please check the sections-distances-terminals-power supply table.

TECHNICAL SPECIFICATIONS

Automatic on: With the monitor on standby, pressing the automatic on button allows to automatically turn on other panels (if there are any):

- With panel 0 of the block corresponding to the monitor.
- With panel 1 of the block corresponding to the monitor.
- With the general entry panel with panel number 0.

Call lengthener or light and bell activator: for direct connection of the call lengthener or light and bell activator in the corresponding terminals.

Screen TFT 4.3".

Resolution: 480 (H) x 272 (V) lines.

SURFACE installation (installed on the wall, the extra-thin profile only protrudes 23mm from the wall, 44mm with arm).

Monitor dimensions: 200 x200x44 (height-width-depth).

Power: 18 VDC

Door release and guard unit call button.

Call volume control

Colour, brightness and contrast control.

Door bell: for direct house call button connection to monitor/telephone.

Selectable call tunes.

Private communication. Conversation secrecy.

Consumption ($\pm 5\%$):

- in standby: 25mA.
- with audio and video: 230mA.

Monitor with OSD display: incorporates a user-friendly menu through graphical icons so that the installer can perform the programming of the monitor functions according to the needs of the installation and also so that users can access the user settings for customization, i.e. the usage profile: brightness and contrast, type and volume of ringtone, additional functions, activate and deactivate silent mode, etc...

Weight: 0,5913 kg

FERMAX

Size of product when packed: 5,1x22,2x20,7 cm

EAN 13: 8424299094052
