



Product Code

F09425

## 4W DUOX PLUS DECODER/ISOLATOR

Reference

9425

EAN

8424299094250

### Description.

#### Description

Floor decoder with 4 outputs. One output for each apartment, allowing up to 3 terminals (monitors/telephones) per apartment.

Several decoders can be installed on each floor.

The decoder is powered directly from the DUOX PLUS bus.

With DIN4 rail mounting and unlike the 10-output decoder, the strips are not removable.

Each output allows the branching distances on the floor to be increased up to 100 m.

In the event of a malfunction (short circuit) of any of the decoder outputs, both the input DUOX PLUS bus and the rest of the outputs will continue to function normally. In addition, when a short circuit occurs in an output, the red led associated with it will light up, thus indicating the output in which the fault has occurred.

It is not necessary to enter the houses to program the address of the terminals since the decoder includes a group of microswitches (dipswitches) to program the addresses of each of its outputs (sequential programming). The decoder addresses can also be programmed non-sequentially (open programming).

#### WHEN IS IT RECOMMENDED TO PLACE THIS INTELLIGENT DECODER?

- When we have to install more than 6 terminals per floor in the building.
- When the distance from the terminals to the trunk is greater than 25 meters or when we do not know this distance.
- When different types of cables are mixed in the same installation or all the cables go to the same point (it is common to find this type of wiring in replacement installations).

## Details.

---

|   |  |
|---|--|
| Packaging measurements (height<br>x width x depth) cm | Video Door Entry system<br>Technologie<br>DUOX |
|---|--|

### Manuals

970269 Decoder-Aislador DUOX PLUS 4S ref 9425 10\_22.pdf