

SY-01SL – High Speed gate



Synel order number -

SY-01SL Side unit – 155087

SY-01SL Center unit - 155088

Features:

- Problem self-recovery and corrective measure ability, convenient maintain and adjust.
- Motherboard with high clean sound read chips which could broadcast in light of user's requirement.
- Human base model indication function, real time displaying, improve the passing rate and convenient maintain.
- Automatic counting indicating passenger's number.
- Resetting automatically, auto cancel the pass through and closed barrier in case nothing passes the channel in a setting time.
- Anti-pinch function with UPS to satisfy firefighter requires, ensure user's safe.
- Break-in, tail, over-pass and reverse alert function in order to keep orderliness and effectively manage.
- Standard input/output port, meanwhile leaving a port space for installing RS485 communication, connect and manage the integrated systems through the remote PC.
- Super combination capacity, adjustable model on site, adjustable speed of barrier slide, Open signal with memory or without set function.

Technical specifications:

Power voltage	AC220±10%, 50Hz	Drive voltage	DC24V 20W
Dimension (Customized Optional)	1400*335*1000m	Communication port	RS485
(Operation condition)	-30°C~+70°C	Material:	SS304 Cover thickness:1.5mm Cabinet thickness:1.2mm
Relative humidity	≤95%, None-condensation	Open direction	Single and Double (optional)
Input signal	12v DC level or 12v pulse>100ms	Gate opening and closing time	0.5s
Working Current	≤2000mA	IP Degree	IP43
Length of the bar	260mm	Width of passage	≤550mm
Pass speed	≤30 person/minutes	Service life	≥5 million times

