

MEET MILO DIGITAL PANEL

Ref. 1832

1.2MPX HD COLOUR CAMERA

Viewing angle: 105° (H) 55° (V)
Camera activation in
low-light conditions
(High powered leds)

HIGH POWERED
LOUDSPEAKER

FERMAX

4,3" GRAPHIC DISPLAY

BACKLIT CAPACITIVE
TOUCH KEYPAD

HIGH-STRENGTH PMMA
TEMPERED GLASS

PRESENCE SENSOR

MIFARE PROXIMITY READER

IP65 IK07

Dimensions: 155 x 380 x 48 mm

MEET
FEEL NO LIMITS FERMALX IP

- Electronic Directory: possibility to upload a custom image, message or logo.
- White list.
- Guest code for temporary visitors.
- Wiegand input/output for third party proximity reader integration.
- Face recognition access control.*
- Up to 4 additional auxiliary IP cameras during conversation.
- Lift control.
- Forced door alarm and tampering alarm.
- Fire alarm with door unblocking and notification.
- Additional IP RTSP video output for NVR recording.
- Access Control Integrated for 100.000 cards* or PIN code.
- Voice Synthesizer.
- Available in 13 languages.

Accessoires

ref.9542: flush box	143x375x58
ref.95171: surface box	160x387x66-108
ref.9512: hood	165x381x50

Technical specifications

Power supply	PoE or 12 Vdc**
Consumption on standby	290 mA
Consumption working	490 mA
Working temperature	-40 to +55 °C

* For the configuration of proximity cards and face recognition, it is required the residential management SW and the key ref.9540.

** In cold places below -20°C use a 12Vdc 2A power supply instead of PoE.

MORE INFO

