

FERMAX



DUOX PLUS CORA PANEL

Ref. 7701

720P WIDE-ANGLE CAMERA
Viewing angle: 120° (H) 80° (V)

MIRROR MODE
(Retroview function).

WAVE OF LEDs
with illumination and movements that signal status.

BACKLIT MECHANICAL KEYPAD
with a dot on the key 5 and embossing on the BELL key.

SPEAKER

5" LCD GRAPHIC DISPLAY
customisable by the installer (images and messages).

LIGHT AND PRESENCE SENSOR

HIGH-QUALITY AUDIO thanks to the CDS (Cora Dynamic Sound) system, which includes 2 digital MEMS microphones.

ANODISED ALUMINIUM PANEL
with no visible screws.

IP65 IK08

Dimensions: 130 x 295,5 x 27,6 mm

DUOX^{plus}

- **Duox Plus technology:** the only **100%** digital Smart System in **2 wires**.
- **Ultra-slim**, only 1 cm thick when flush mounted and 3 cm when surface mounted.
- **Simple** and intuitive **installation** with 1 screw.
- **Advanced processor** with 4-core CPU+GPU.
- **Multi-language voice synthesiser** (32 languages), bilingual message configuration and customisable language.
- Assisted **alphanumeric dialling**.
- **Possibility to create backup copies** of users and configuration.
- **High-quality audio** thanks to the **CDS (Cora Dynamic Sound)** system which filters out environmental noise.
- **Access control** via keypad and integrated (EM 125Khz) proximity reader.
- **Configuration from mobile, tablet or computer**, via a web server without having to open the panel.
- Built-in **DUOX PLUS installation tester**. It creates an installation status report in PDF format.
- An optional **inductive loop** can be connected for people with hearing aids. (ref. 7722).

Accessories

ref.7703: flush box	115x280x45
ref.7709: surface box	130x295,5x20
ref.7706: simple frame	225x415x3
ref.7705: hood (flush and surface)	130x12x31

Technical specifications

Power supply	24-18 Vcc
Consumption on standby	200-320 mA
Consumption working	500-780 mA
Working temperature	-25 to 55 °C

MORE INFO



cora
by FERMAL